

PDP - 4360HD

43" HIGH DEFINITION PLASMA TELEVISION

- High Definition XGA Resolution (1,024 x 768p)
- 43" Diagonal / 16:9 Wide-Screen Aspect Ratio
- Brightness:
- Contrast:
- 3000:1

PANEL TECHNOLOGY

- Deep Encased Cell Structure, This energy design allows each pixel to deliver a more concentrated beam of light, for truer color and brighter images
- Pure Crystal Emissive Layer, panel technology for dynamic color and contrast, extremely black black's and increased brightness
- 1st Surface Pure Color Filter, for improved contrast and the most accurate color reproduction. The non-glass filter is bonded directly to the plasma panel reducing light reflection and refraction for a more accurate image

VIDEO PROCESSING TECHNOLOGY

- PureDrive II Signal Processing Full Time 10bit Digital Video Processing, delivers a low noise, high contrast, natural color image
 - New ACE IV (Advanced Continuous Emission), for billions of color reproduction and improved grey-scale rendering in dark picture areas.
 - Advanced PureCinema with 3:3 Pull Down, film-based material on DVD, videotape or even regular TV will match the smooth and natural reproduction you'd see in a theater.
 - Color Temperature Adjustment, 3 Settings (High/Mid/Low)
 - Digital Noise Reduction (4 settings off / high / mid / low)
 - MPEG Noise Reduction
 - **Digital CTI** (Color Transient Improver)
 - Natural Resize
 - Natural Enhancer
 - Digital Croma Decoder, 10-bit

CONVENIENCE FEATURES

- Separate Media Receiver for Advanced Connectivity and Flexible Set-up. All source products connected directly to Media Receiver with one proprietary digital interface cable to plasma panel.
- Built-in TV Tuners, for receiving over-the-air High Definition and Standard Definition Broadcasts.
 - Dual NTSC Tuners and ATSC Tuner
 - Digital Cable Ready (DCR) with CableCARD[™] Interface
- TV Guide On Screen Interactive[®] Program Guide for easy navigation of TV program services
- V-Chip Parental Control (Supporting MPAA & TV Parental Guidelines)
- Aspect Ratio Control (5 position Wide / Zoom / Cinema / Full / 4:3) – "Dot by Dot" for PC
- Wide Viewing Angle (160 Degree Horizontal and Vertical)
- Split Screen / Picture in Picture Multi-Window Display Modes for on-screen viewing multiple source at one time
- AV Selection Memory (5 position Std / Dynamic / Movie / Game / User)
- Full Function Preset and Learning Remote Control





Media Receiver and Table Top Stand Included

1,100 cd/m²

Pioneer

PDP - 4360HD

43" HIGH DEFINITION PLASMA TELEVISION

VERSITILE VIDEO AND AUDO CONNECTIVITY

• Inputs:

- Antenna F Connections x 2 (1-Digital & Analog / 1-Analog)
- HDMI with HDCP x 2
- Component x 3, (2 on rear / 1 on front)
- AV Composite x 3 (2 on rear / 1 on front)
- S-Video x 3 (2 on rear / 1 on front)
- i.Link x 2 (For use with DVHS)
- D-Sub for PC x 1 (Front)
- SR In x1
- CableCARD™ Interface (rear)

• Outputs:

- Optical Audio Output x 1
- Subwoofer Output x 1
- Monitor Output x 1 (Composite)
- SR+ Output x 1

SOUND TECHNOLOGY

- 13 watt x 2 stereo amplifier with separate bass and treble controls
- 2-Way Stereo Speakers
- SRS / FOCUS / TruBass Surround Sound Audio Processing for a virtual sound TV Experience

OTHER

- Table Top Stand (Supplied)
- 3-Meter Digital Connection Cable (Supplied)
- Wall Bracket, Tilt Wall Bracket (Optional)
- 10-Meter Digital Connection Cable (Optional)
- 30-Meter Fiber Optic Connection Cable (Optional)

DIMENSIONS(W x H x D)

- Display (Only): 42.4" x 24.9" x 3.6"
- Media Receiver:16 9/16"x3 9/16"x11 13/16"

WEIGHT:

- Display: 56.9lbs
- Media Receiver:9.9 lbs











DISCLAIMERS

- · Specifications and design subject to modification without notice.
- High-Definition Television (ĤDTV): HDTV refers to a complete product/system with the following minimum performance attributes • Receiver: Receives ATSC terrestrial digital transmissions and decodes all ATSCTable 3 video formats • Display Scanning Format: Has active vertical scanning lines of 720 progressive (720p), 1,080 interlaced (1,080i) or higher • Aspect Ratio: Capable of displaying a 16:9 image • Audio: Receives and reproduces, and/or outputs Dolby Digital audio " Consumer Electronics Association, August 2000
- Displaying the same still images for long periods should be avoided as image shadowing or burn-in may occur.
- Plasma Display Systems display images consisting of hundreds of thousands of minute pixels (light emitting cells), and there is a possibility of inactive, flashing or continually illuminated pixels.
- Plasma Display Systems emit slight amounts of IR (Infrared Emission) through luminous discharge technology. This IR (Infrared Emission) is not harmful to living organisms, but may interfere with the operation of remote controls for other equipment, or cause static in equipment using IR (Infrared Emission) (such as cordless headphones or cordless microphones)

- All phosphor-based display systems (Cathode Ray Television Systems, both direct view televisions and projection televisions as well as plasma display systems) may possibly have image retention, also known as burn-in. Recommended guidelines are as follows:
 - Do not display static images for long periods (such as still images, fixed images from PC or TV game equipment, and/or fixed images such as time of day indicator or channel logo display).
 - Do not display content in the 4:3 aspect ratio (black or gray bars on left and right side of content) or letter-box content (black bars above and below of content) for extended periods of time, or use either of these viewing modes repeatedly within a short period of time. This Plasma Display System is equipped with multiple wide-screen viewing modes; use one of these screen modes to fill the entire screen with content.
 - Displaying dark images after displaying still images for a period of time may cause image retention. In most cases, the image retention can be corrected by displaying bright images for a similar period of time. However, if your Plasma Display System displays still images for additional long periods of time, image retention may be irreparable
 - Plasma Display Systems may have a negative effect on sound or images coming from AM radios, PCs or video-related products.

- Plasma Display Systems are made of glass; be sure to secure it from damage from impact.
- Plasma Display Systems, while in use, may generate some functional sounds, for example: fan motor noise, and electrical circuit humming/glass panel buzzing.
- Plasma Display Systems emit slight amounts of IR (Infrared Emission) through luminous discharge technology. This IR (Infrared Emission) is not harmful to living organisms, but may interfere with the operation of remote controls for other equipment, or cause static in equipment using IR (Infrared Emission) (such as cordless headphones or cordless microphones).
- The Plasma Display System Media Receiver uses an on-board cooling fan. If the
 ambient temperature of the Media Receiver becomes high, the speed of the cooling fan
 increases and it may sound louder than normal during the cooling period.
- PIONEER, the Pioneer Logo, the Elite logo and PureVision are registered trademarks of Pioneer Corporation.
- CableCARDTM is a trademark of Cable Television Laboratories, Inc.
- *Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.
- HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.
- i.LINK and the i.LINK logo are trademarks of Sony Corporation.
- · SRS, TruBass and FOCUS are trademarks of SRS Labs, Inc.
- In the United States, TV Guide and other related marks are registered marks of Gemstar-TV Guide International, Inc. and/or one of its affiliates.